

<i>overall outside length (m)</i>	<i>9,98</i>
<i>width (m)</i>	<i>3,25</i>
<i>weight (kg)</i>	<i>1.800</i>
<i>people capacity</i>	<i>20</i>
<i>maximum power (kW)</i>	<i>457</i>
<i>engine</i>	<i>n. 2 FB XL</i>
<i>CE homologation</i>	<i>B</i>



Standard equipment

Bow nose in fiberglass complete with 3 bits and anchor winch rollers. Big bitt mooring rope holder, Driver's console with hydraulic wheelhouse. Steering wheel, Electric horn recessed. Navigation lights. Self emptying deck. Sink, Windscreen, Stainless steel manrope and handle. Start lights equipment, 50 liters refrigerator, Electrical installation with 12 function user panel and 12V outlet, Driver's seat with manrope, Electric servo control for aft peak opening, Teak sump inserted in the pilot and back seat, 500W electric pulley (complete with 7,5kg anchor, 50m chain and a chain counting instrument), Fractionation for objects inside the aft peak, Compass, Full set of luxury cushions, Stern dashboard with climbing ladder, Stainless steel fueling tanks (320+320 liters) with electrovalves, filters and float, Eyebolts, Shower equipment with 200 liters tank, Electric inflator, Repair kit, Paddles/oars, Bilge pump

Optional equipment

Dinghy cover,
 Console and driver's seat cover,
 Dinghy cover for transport or parking,
 Kitchen,
 Oval teak table with stainless steal,
 Tool chain counter anchor,
 Hangers launching/hauling,
 Stainless steel T Top with cover,
 T Top steel covered with fiberglass complete instruments,
 T Top extender (requires T Top),
 Sundeck extension,
 Courtesy lights treading surface,
 Battery charging equipment and 25A quay outlet,
 Bow propeller with joystick,
 Stern propeller with joystick,
 Stereo system with CD or iPod,
 Extension teak cockpit,
 Second climbing ladder

